

TP80C 3" Thermal Receipt Printer

- Brand New Finished
- Front Paper Loading, Space Saving
- Dual-blade Cutter Equipped
- Up to 200mm/s Printing Speed
- 576 dots TPH for 72mm Printing Width



Front Paper Loading,
Easy Paper Loading



Front Paper Exit



Specification

Item	Parameter	
Printing	Printing Method	Direct thermal line printing
	Resolution	Default 203 dpi, 180 dpi can be emulated
	Printing Width	72mm(576dots)
	Printing Speed	Max. 200mm/s
	Printing Density	Adjustable from degree 1 to degree 4
	Printing Direction	Vertical and horizontal
Interface	Default	Built-in USB, RS232, LAN
Auto cutter		Partial Cut
Page mode		YES
Memory	RAM	2MB
	Flash	4MB
Character set	Font	Font A:12*24 Font B:9*17 CHN: 24*24
	Number of Columns	48/64
	Alphanumeric	95
	Code page	19
Graphics		Support bitmap printing with different density and user defined bitmap printing (Max. 40K for per bitmap, and Max. 256K for total)
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, PDF417
Detection	Sensor	Paper out, Cover Open, Cutter Jam

Power supply	Input	AC100V-240V 50-60HZ
	Output	DC 24V±5%, 2.0A,
Paper	Paper Loading	Up loading, Easy loading
	Paper Type	Standard thermal paper
	Paper Width	79.5±0.5mm
	Paper Thickness	0.056~0.13mm
	Paper Roll Diameter	Max. 83mm
Condition	Operating	0~45°C/10~85%RH
	Storage	-20~60°C/10~90%RH
Reliability	TPH Life	100km
	Cutter Life	1,000,000 times
	Motor Life	360,000 hours
Accessories		Power adaptor, RS232 cables, CD, Quick Guide, paper roll
Emulation		ESC/POS
Driver		Windows (Win10/POSReady/Win8/Win7/XP), Linux, OPOS
Certifications		CE/CCC
Eco Features		Paper saving mode

